



TYPICAL PLAN FOR RECREATIONAL HARD COURT LAYOUT

NOTES

1. BACKBOARD RING AND TOWER CONFIGURATION INSTALLED TO MANUFACTURERS INSTRUCTIONS, REFER TO BASKETBALL RING AND TOWER DETAIL S-1020.
2. ALL LINE MARKING TO BE 50MM WIDE.
3. FINISHED SURFACE LEVEL TO BE 50MM ABOVE EXISTING GROUND LEVEL.
4. TOP OF BASKETBALL RING TO BE 3050MM ABOVE PLAYING SURFACE.
5. ALL NUTS AND BOLTS TO BE GALVANISED ISO METRIC THREAD.
6. PAINTED COURT CONFIGURATION COULD VARY WITH SCALE OF PLAY REQUIRED AND SIZE PROVIDED.
7. ENSURE ORIENTATION OF DIRECTION OF PLAY IS ALONG A NORTH-SOUTH AXIS, PLACE BASKETBALL TOWER AT SOUTHERN END.
8. REFER TO 'TRULINE' CATALOGUE, OR SIMILAR, FOR MORE INFORMATION AND DIMENSIONS. DIMENSIONS WILL VARY WITH SIZE OF HARD COURT.

CITY OF CASEY

RECREATIONAL ELEMENTS
HARD COURT LAYOUT DETAIL

MANAGER OF ENGINEERING &
ENVIRONMENTAL SERVICES
LAST UPDATE 09.11.2012

AMENDMENTS:

S-1019